



TEXAS PNEUMATIC TOOLS, INC.

MOISTURE SEPARATING SYSTEMS A.S.M.E. CERTIFIED



- Features**
- ◆ Eliminates moisture from the compressor with four levels of separation
 - ◆ No moving parts to maintain
 - ◆ Deliquescent desiccant for added drying
 - ◆ Multiple outlets
 - ◆ Use in combination with additional Manifolds or Portable FRL Systems

SPECIFICATIONS

MODEL #	CAPACITY	WEIGHT	HEIGHT	LENGTH	WIDTH	TANK DIAMETER	INLET SIZE	MAX CFM	WORKING PRESSURE	TEST PRESSURE	CONNECTOR DETAILS*
TX-MSS-400	15 Gallon 57 Liters	424 lbs 192 kg	58" 147 cm	55" 140 cm	42" 107 cm	12" 305 mm	2" 51 mm	400 11,327 l/min	200 psi 14 Bar	260 psi 18 Bar	INLET: 4-Prong crowfoot. OUTLETS: Safety auto exhaust ball valve w/ locking handle & 2-Prong crowfoot & 4-Prong crowfoot
TX-MSS-800	30 Gallon 114 Liters	526 lbs 239 kg	63" 160 cm	55" 140 cm	42" 107 cm	16" 406 mm	2" 51 mm	800 22,653 l/min	200 psi 14 Bar	260 psi 18 Bar	INLET: 4-Prong crowfoot. OUTLETS: Safety auto exhaust ball valve w/ locking handle & 2-Prong crowfoot & 4-Prong crowfoot
TX-MSS-1600	60 Gallon 227 Liters	1235 lbs 560 kg	74" 188 cm	69" 175 cm	49" 125 cm	20" 508 mm	3" 76 mm	1600 45,307 l/min	200 psi 14 Bar	260 psi 18 Bar	INLET: 3" "BOSS" wing nut thread. OUTLETS: Safety auto exhaust ball valve w/ locking handle & 2-Prong crowfoot, 4-Prong crowfoot & 3" "BOSS" wing nut thread.

~ Made in U.S.A. ~

(*) Safety lock cable included with all Inlet / Outlet connections.

www.airtools.com

Email: tptinfo@airtools.com

TEXAS
1-800-231-9740
254-587-2533 (Int'l calls)

NEVADA
1-800-858-1222

VIRGINIA
1-800-626-1091



Air Flow Check Valves



**Safety Lock Cables
TX-SLC1 & TX-SLC2**



Portable FRL Systems from 1/2" to 1-1/2" NPT